

## **NOTICE INVITING BUDGETORY OFFERS**

Name of Work	" Filtration, hot oil circulation,Furan and Dissolved Gas analysis of transformers installed at Port"
Date of submission of budgetary quotation	On or before <b>12/03/2025<del>.</del></b>
Budgetary offer no	CME/XEN (E-HR)/ 25/B6
	Executive Engineer (E-HR),
	2nd floor, Mechanical Engineering Department,
	Mormugao Port Authority,
Address for	Admin. Building,
communication:	Headland sada
	Vasco-de-Gama
	Goa - 403804
	Phone : (0832) 2594207, 2594577
Contact Details	Email : mohamed.shaik@mptgoa.gov.in
Website	www.mptgoa.gov.in

# EXECUTIVE ENGINEER (E-HR) MORMUGAO PORT AUTHORITY



Name of work: "Filtration, hot oil circulation, Furan and Dissolved Gas analysis of transformers installed at Port "

## **TECHNICAL SPECIFICATIONS**

## 2.0 GENERAL

Mormugao Port Authority proposes to carry out the work of Filtration, hot oil circulation Furan and Dissolved Gas analysis of 22 oil type transformers installed at Port at various locations in the Port along with calibration of Buchholz relay of transformer.

## 2.1 SCOPE OF WORK

- 2.1.1 Filtration, hot oil circulation and Dissolved gas analysis of 22 nos transformer has to be carried out on the power transformers as per the list enclosed at BOQ. Transformer should be switched off during the filtration process and the connected breaker has to be ensured to be pulled out.
- 2.1.2 The On Line Tap Changer (OLTC) oil has to be filtered and topped up as required.
- 2.1.3 The transformer tank, core and winding has to be cleaned with hot oil circulation at 50 C and cleaning oil to be drained out.
- 2.1.4 Dehydration of transformer winding should be done to remove moisture from the core and windings.
- 2.1.5 On completion of hot oil, circulation / filtration, the oil should be tested for dielectric strength for not less than 30 KV (BDV) for one minute with 2.5mm gap. Testing has to be carried out in the presence of Engineer-in-charge.
- 2.1.6 After completion of work, the transformer has to be put back in service and the normal functions of transformers shall be demonstrated satisfactorily to the site in-charge.
- 2.1.7 Transformer oil required for topping up/filling shall be supplied by the Port.
- 2.1.8 Disposal of old removed oil is in the scope of contractor.



- 2.1.9 The contractor has to supply and replace the Silica gel of all the transformers.
- 2.1.10 The contractor shall make his own Transportation arrangement for shifting of Transformer oil filtration unit in different location of transformer available in the Furnishing Division.
- 2.1.11 The dissolved gas and furan analysis of all transformer has to be carried out and certificates submitted accordingly.
- 2.1.12 The calibration of Buchholz relay, transformer oil testing equipment, winding temperature indicator and Oil temperature indicator has to be carried out and the required calibration certificate has to be provided by the contractor.
- 2.1.13 Contractor shall ensure that three are no oil leakages and should arrest if any
- 2.1.14 The gaskets of 7 no's of transformer indicated in the BOQ has to replaced in order to arrest the oil leakage. The gasket replacement work includes:
  - a. Removal of top cover of transformer by disconnecting the Bus duct.
  - b. Drain the transformer oil from unit to suitable container so as to refill it back.
  - c. Arresting the oil leakage at transformer by replacing gasket at top cover, Buchholz relay, tap changer mechanism, HT LT bush, drain plug etc.(**Supply of gasket is in the contractor scope**)
  - d. Refitting the top cover with proper gaskets and necessary fastener to firmly secure the removed cover.
- 2.1.15 The contractor shall take adequate care while carrying out above work in such a way not to damage the components/spares in the transformers.
- 2.1.16 All other items / material which are required for completion of the work shall be supplied by the contractor.
- 2.1.17 After successful completion of the work, the contractor shall submit the test reports along with calibration certificates. The necessary Testing instruments shall have valid calibration certificates traceable to national or international standards, the same has to be submitted to MPA.



# 3) Qualification Criteria:

- i. Only Electrical contractors possessing a valid Electrical license to work on minimum 650V lines issued by the licensing board shall be eligible to quote for the enquiry.
- ii. The Bidder shall have successfully carried out work of Filtration of transformer oil during last 7 (Seven) years ending last day of month previous to the one in which quotations are invited for Central Govt. / State Govt. / Port Sector / PSU or any reputed organization.

## 4) **COMPLETION PERIOD:**

All the jobs as per contract, have to be completed within **60 days** from the date of issue of letter of acceptance.

## 5) SPECIAL TERMS AND CONDITIONS

- i. The Contractor shall commence and complete the work as per the BOQ and technical specifications. The work and quantity is to be carried out as per the site conditions and relevant IS standards.
- ii. The Contractor shall complete the work in all respect to the satisfaction of the Engineer-In-Charge or his representative.
- **iii.** The work should be carried out with utmost safety precaution with minimum possible disruption of power supply. The contractor has to ensure that that cables are disconnected on both the sides.

## 6) OTHER TERMS AND CONDITIONS

- i. The firm is advised to visit the site and get acquainted regarding the nature of the work involved at site conditions before quoting the offer.
- **ii.** The firm should engage skilled service personnel with the relevant required tools and instruments for commissioning the same.
- iii. The Contractor personnel engaged in the work shall follow all safety, security



and General Rules enforced by Mormugao Port Authority (MPA) and the firm will only be responsible for the same.

- iv. MPA will not be responsible for any loss or damage of the men / materials / tools / plants engaged by the firm during the work at site / transportation.
- v. No advance payment will be made.
- vi. Final payment will be made only after satisfactorily completion of the work.
- vii. Necessary entry passes shall be obtained by the firm at their own cost with the approval of Port Officials.
- viii. Necessary electrical power supply required for testing of cables will be provided by MPA at free of cost at nearest possible point. However, the firm should make his own arrangements to take power supply from the nearest source of supply.



## PRICE SCHEDULE (BILL OF QUANTITIES - BOQ)

Name of the Work: "Filtration, hot oil circulation of 22 oil type transformers installed at Port"

Sr.N	Description	11	0	Rate/Unit	Applicable GST %	Amount
0	Description	Unit	Quantity	<b>(Rs.)</b> In Fig	631 %	(Rs)
I	Filtration and hot oil circulation of 22 transformers			g_		
1.	2 nos of 5MVA, 33KV/ 3.3KV, Transformers at Substation A. Make:- Electric Transformer and Equipment (4800 Litres per transformer)	litre	9600			
2.	1 no of 2MVA, 33KV/440V, Power Factor Correction transformer at Substation A, Make:- Trinity Transformer Industry (1900 Litres)	litre	1900			
3.	3 nos of 630 KVA , 3.3KV/ 415 V, Transformers at Substation A. Make:- NGEF (1144 Litres per transformer)	litre	3432			
4.	2 nos of 315 KVA, 3.3KV/ 415 V, Transformer at Berth no. 10. Make:- 1 no. The Indian Transformers Ltd. And 1 no. NGEF (450 Litres per transformer)	litre	900			
5.	1 no of 500 KVA, 3.3KV/ 415 V, Transformer at Berth no. 10. Make:- Pactil Transformer (545 Litres)	litre	545			
6.	1 no of 630 KVA, 3.3KV/ 433 V Transformer at Jetty Substation. Make:- Kirloskar Electric Co. Ltd (1250 litres)	litre	1250			
7.	1 no of 500 KVA, 3.3KV/415V Transformer at Jetty Substation. Make:- The Indian Transformers Ltd (490 litres)	litre	490			
8.	2 no of 500 KVA, 11KV/433 V, Transformer at Harbour Substation Make:- Current Electricals Ltd. (710 Litres per transformer)	litre	1420			
9.	1 no. 630 KVA transformers 3.3 KV	litre	1040			



/ 415 V       containing 1040 litres at Administrative Building S/s.         10.       2 no. 800 KVA transformers 11 KV / 415 V each at Administrative Building S/s. containing 1010 Litres per transformer       litre       2020         11       1 no. 650 KVA, 415 V Automatic voltage Regulator(AVR) containing 800 Litres at Administrative Building S/s       litre       800         12       1 no. 250 KVA, 11 KV / 433V transformer containing 465 Litres at Baina W/S S/s       litre       465         13       1 no. 500 KVA transformer 11 KV / 415 V containing 610 Litres at Headland S/s       litre       610         14       1 no. 100 KVA transformer 11 KV / Automatic voltage Regulator (AVR) containing 915 Litres at Headland S/s       litre       915         15       1 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/s       litre       490         16       1 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/s       litre       355         16       1 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/s       litre       325         11       Replacement of silica GEL in transformers       kg       22         11       Dissolved Gas and Furan Gas Analysis of transformers       no       22         11       Dissolved Gas and Furan Gas Analysis of transformers       no       40 <th></th> <th></th> <th></th> <th></th> <th></th> <th></th>						
10.       2 no. 800 KVA transformers 11 KV / 415 V each at Administrative Building S/s. containing 1010 Litres per transformer       litre       2020         11       1 no. 650 KVA, 415 V Automatic voltage Regulator(AVR) containing 800 Litres at Administrative Building S/s       litre       800         12       1 no. 250 KVA, 11 KV / 433V transformer containing 465 Litres at Baina W/S S/s       litre       465         13       1 no. 500 KVA transformer 11 KV / 415 V containing 610 Litres at Headland S/s       litre       610         14       1 no. 1000 KVA transformer 11 KV / Automatic voltage Regulator (AVR) containing 915 Litres at Headland S/s       litre       915         15       1 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/s       litre       490         16       1 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/s       litre       355         16       1 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/s       litre       325         II       Replacement of silica GEL in transformers       kg       22       11         III       Dissolved Gas and Furan Gas Analysis of transformers       no       22       11         III       Dissolved Gas and Furan Gas Analysis of transformers       no       22       11         III       Calibration of Winding temperature indicator or Oil tem						
/ 415 V each at Administrative Building S/s. containing 1010 Litres per transformer       litre       2020         11       1 no. 650 KVA, 415 V Automatic voltage Regulator(AVR) containing 800 Litres at Administrative Building S/s       litre       800         12       1 no. 250 KVA, 11 KV / 433V transformer containing 465 Litres at Baina W/S S/s       litre       465         13       1 no. 500 KVA transformer 11 KV / 415 V containing 610 Litres at Headland S/s       litre       610         14       1 no. 1000 KVA transformer 11 KV / Automatic voltage Regulator (AVR) containing 915 Litres at Headland S/s       litre       915         15       1 no. 500 KVA/ 415V Automatic voltage Regulator (AVR) containing 490 Litres at Headland       litre       490         16       1 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 335 Litres at Hospital S/s       litre       355         II       Replacement of silica GEL in transformers       kg       22       litres/ analysis of transformers         III       Dissolved Gas and Furan Gas Analysis of transformers       no       22       litres/ analysis of transformers         IV       Calibration of Winding temperature indicator or Oil temperature indicator or Oil temperature       40       40						
Building S/s. containing 1010 Litres per transformer       Ittre       2020         11       1 no. 650 KVA, 415 V Automatic voltage Regulator(AVR) containing 800 Litres at Administrative Building S/s       Iitre       800         12       1 no. 250 KVA, 11 KV / 433V transformer containing 465 Litres at Baina W/S S/s       Iitre       465         13       1 no. 500 KVA transformer 11 KV / 415 V containing 610 Litres at Headland S/s       Iitre       610         14       1 no. 1000 KVA transformer 11 KV / 415 V containing 915 Litres at Headland S/s       Iitre       915         15       1 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Headland S/s       Iitre       490         16       1 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/s       Iitre       355         16       1 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/s       IItre       355         II       Replacement of silica GEL in transformers       kg       22       11         III       Dissolved Gas and Furan Gas Analysis of transformers       no       22       11         III       Calibration of Winding temperature indicator or Oii temperature indicator or Oiii temperature indicator or Oii temperature	10.					
Building S/S. containing 1010 Litres         per transformer         11       1 no. 650 KVA, 415 V Automatic         voltage Regulator(AVR) containing         800         12       1 no. 250 KVA, 11 KV / 433V         transformer containing 465 Litres at         Baina W/S S/s         13       1 no. 500 KVA transformer 11 KV /         415       V containing 610 Litres at         Headland S/s         14       1 no. 1000 KVA transformer 11 KV /         Atto Noto Regulator (AVR)         containing 915 Litres at Headland         S/s         15       1 no. 500 KVA transformer 11 KV /         415 V containing 490 Litres at         Hitre       915         S/s         15       1 no. 500 KVA transformer 11 KV /         415 V containing 490 Litres at         Hospital S/s         16       1 no. 500 KVA/ 415V Automatic         voltage Regulator(AVR) containing         355 Litres at Hospital S/s         II       Replacement of silica GEL in         kg       22         III       Dissolved Gas and Furan Gas         Analysis of transformers       no         10       Calibration         a. Calibration of Winding			litre	2020		
11       1       no. 650 KVA, 415 V Automatic voltage Regulator(AVR) containing 800 Litres at Administrative Building S/s       litre       800         12       1       no. 250 KVA, 11 KV / 433V transformer containing 465 Litres at Baina W/S S/s       litre       465         13       1       no. 500 KVA transformer 11 KV / 415 V containing 610 Litres at Headland S/s       litre       610         14       1       no. 1000 KVA transformer 11 KV / Automatic voltage Regulator (AVR) containing 915 Litres at Headland S/s       litre       915         15       1       no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/s       litre       490         16       1       no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/s       litre       355         II       Replacement of silica GEL in transformers       kg       22       11         II       Dissolved Gas and Furan Gas Analysis of transformers       no       22         IV       Calibration       itemperature indicator or Oil temperature indicator or Oil temperature       no       40			intro	2020		
voltage Regulator(AVR) containing 800 Litres at Administrative Building S/s       litre       800         12       1 no. 250 KVA, 11 KV / 433V transformer containing 465 Litres at Baina W/S S/s       litre       465         13       1 no. 500 KVA transformer 11 KV / 415 V containing 610 Litres at Headland S/s       litre       610         14       1 no. 1000 KVA transformer 11 KV / Automatic voltage Regulator (AVR) containing 915 Litres at Headland S/s       litre       915         15       1 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/s       litre       490         16       1 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/s       litre       355         II       Replacement of silica GEL in transformers       kg       22       11         III       Dissolved Gas and Furan Gas Analysis of transformers       no       22       11         III       Dissolved Gas and Furan Gas Analysis of transformers       no       22       11         III       Calibration       40       40       40						
800       Litres       at       Administrative       Ittle       800         12       1       no. 250       KVA, 11       KV / 433V       Ittle       465         12       1       no. 250       KVA, 11       KV / 433V       Ittle       465         13       1       no. 500       KVA transformer 11       KV /       415       V       containing       610         14       1       no. 1000       KVA transformer 11KV       Ittre       610       610         14       1       no. 1000       KVA transformer 11KV       Ittre       915       610         14       1       no. 1000       KVA transformer 11KV /       Automatic voltage Regulator (AVR)       Ittre       915         15       1       no. 500       KVA transformer 11 KV /       415       V       ontaining 490       Litres       490         15       1       no. 500       KVA transformer 11 KV /       415       V       ontaining 490       Litres       490         16       1       no. 500       KVA 415V       Automatic       V       355       Ittre       355         11       Replacement of silica       GEL in       kg       22       111	11	-				
800       Liftes at Administrative         Building S/s         12       1 no. 250 KVA, 11 KV / 433V transformer containing 465 Liftes at Baina W/S S/s       lifte       465         13       1 no. 500 KVA transformer 11 KV / 415 V containing 610 Liftes at Headland S/s       lifte       610         14       1 no. 1000 KVA transformer 11 KV / Automatic voltage Regulator (AVR) containing 915 Liftes at Headland S/s       lifte       915         15       1 no. 500 KVA transformer 11 KV / 415 V containing 490 Liftes at Hospital S/s       lifte       490         16       1 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Liftes at Hospital S/s       lifte       355         II       Replacement of silica GEL in transformers       kg       22         III       Dissolved Gas and Furan Gas Analysis of transformers       no       22         IV       Calibration       a.       calibration of Winding temperature indicator or Oil temperature       no       40			litre	800		
12       1 no. 250 KVA, 11 KV / 433V transformer containing 465 Litres at Baina W/S S/s       litre       465         13       1 no. 500 KVA transformer 11 KV / 415 V containing 610 Litres at Headland S/s       litre       610         14       1 no. 1000 KVA transformer 11 KV / Automatic voltage Regulator (AVR) containing 915 Litres at Headland S/s       litre       915         15       1 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/s       litre       490         16       1 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/s       litre       355         II       Replacement of silica GEL in transformers       kg       22         III       Dissolved Gas and Furan Gas Analysis of transformers       no       22         IV       Calibration       a. Calibration of Winding temperature indicator or Oil temperature       no       40			intro	000		
transformer containing 465 Litres at Baina W/S S/slitre465131 no. 500 KVA transformer 11 KV / 415 V containing 610 Litres at Headland S/slitre610141 no. 1000 KVA transformer 11 KV Automatic voltage Regulator (AVR) containing 915 Litres at Headland S/slitre915151 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/slitre490161 no. 500 KVA/ tansformer 11 KV / 415 V containing 490 Litres at Hospital S/slitre355161 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/slitre35511Replacement of silica GEL in transformerskg2211Dissolved Gas and Furan Gas Analysis of transformersno221VCalibration40						
Baina W/S S/s131 no. 500 KVA transformer 11 KV / 415 V containing 610 Litres at Headland S/slitre610141 no. 1000 KVA transformer 11KV Automatic voltage Regulator (AVR) containing 915 Litres at Headland S/slitre915151 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/slitre490161 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/slitre355161 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/slitre35511Replacement of silica GEL in transformerskg2211Dissolved Gas and Furan Gas Analysis of transformersno221VCalibrationno40	12	-				
13       1 no. 500 KVA transformer 11 KV / 415 V containing 610 Litres at Headland S/s       litre       610         14       1 no. 1000 KVA transformer 11KV Automatic voltage Regulator (AVR) containing 915 Litres at Headland S/s       litre       915         15       1 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/s       litre       490         16       1 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/s       litre       355         II       Replacement of silica GEL in transformers       kg       22         III       Dissolved Gas and Furan Gas Analysis of transformers       no       22         IV       Calibration       a. Calibration of Winding temperature indicator or Oil temperature       no       40			litre	465		
415 V containing 610 Litres at Headland S/slitre610141 no. 1000 KVA transformer 11KV Automatic voltage Regulator (AVR) containing 915 Litres at Headland S/slitre915151 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/slitre490161 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/slitre35511Replacement of silica GEL in transformerskg2211Dissolved Gas and Furan Gas Analysis of transformersno221VCalibrationno40						
Headland S/sImage: Second	13					
141 no. 1000 KVA transformer 11KV Automatic voltage Regulator (AVR) containing 915 Litres at Headland S/slitre915151 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/slitre490161 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/slitre35511Replacement of silica GEL in transformerskg2211Dissolved Gas and Furan Gas Analysis of transformersno221VCalibration40			litre	610		
Automatic voltage Regulator (AVR) containing 915 Litres at Headland S/slitre915151 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/slitre490161 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/slitre355IIReplacement of silica GEL in transformerskg22IIIDissolved Gas and Furan Gas Analysis of transformersno22IVCalibration40						
containing 915 Litres at Headland S/sIltre915151 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/slitre490161 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/slitre355IIReplacement of silica GEL in transformerskg22IIIDissolved Gas and Furan Gas Analysis of transformersno22IVCalibration40	14					
containing 915 Litres at Headland S/s       Ites at Headland S/s       Ites at Headland S/s         15       1 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/s       Iter       490         16       1 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/s       Iter       355         II       Replacement of silica GEL in transformers       kg       22         III       Dissolved Gas and Furan Gas Analysis of transformers       no       22         IV       Calibration       Itemperature indicator or Oil temperature       40		<b>0 0</b> ( )	litre	915		
151 no. 500 KVA transformer 11 KV / 415 V containing 490 Litres at Hospital S/slitre490161 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/slitre355IIReplacement of silica GEL in transformerskg22IIIDissolved Gas and Furan Gas Analysis of transformersno22IVCalibrationa.Calibration of Winding temperature indicator or Oil temperatureno40						
415 V containing 490 Litres at Hospital S/slitre490161 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/slitre355IIReplacement of silica GEL in transformerskg22IIIDissolved Gas and Furan Gas Analysis of transformersno22IVCalibrationa.Calibration of Winding temperature indicator or Oil temperatureno40						
Hospital S/sImage: Constraint of the second sec	15		l'tra-	100		
161 no. 500 KVA/ 415V Automatic voltage Regulator(AVR) containing 355 Litres at Hospital S/slitre355IIReplacement of silica GEL in transformerskg22IIIDissolved Gas and Furan Gas Analysis of transformersno22IVCalibrationa.Calibration of Winding temperature indicator or Oil temperatureno40			litre	490		
voltage Regulator(AVR) containing 355 Litres at Hospital S/slitre355IIReplacement of silica GEL in transformerskg22IIIDissolved Gas and Furan Gas Analysis of transformersno22IVCalibration22a.Calibration of Winding temperature indicator or Oil temperatureno40	16					
355 Litres at Hospital S/s       II       Replacement of silica GEL in transformers       kg       22         III       Dissolved Gas and Furan Gas Analysis of transformers       no       22         IV       Calibration       IV       Calibration of Winding temperature indicator or Oil temperature       no       40	10		litro	255		
IIReplacement of silica GEL in transformerskg22IIIDissolved Gas and Furan Gas Analysis of transformersno22IVCalibration22IVCalibration of Winding temperature indicator or Oil temperatureno40			nue	300		
transformers     kg     22       III     Dissolved Gas and Furan Gas Analysis of transformers     no     22       IV     Calibration     22       IV     Calibration of Winding temperature indicator or Oil temperature     no     40						
III       Dissolved Gas and Furan Gas Analysis of transformers       no       22         IV       Calibration	11		kg	22		
Analysis of transformers     no     22       IV     Calibration     IV       a.     Calibration of Winding temperature indicator or Oil temperature no     40						
IV     Calibration       a.     Calibration of Winding temperature indicator or Oil temperature no	111		no	22		
a.Calibration of Winding temperature indicatorno40	IV/					
indicator or Oil temperature no 40						
	а.	•	no	40		
		indicator of transformer	110	10		
b Calibration of Buchholz relay of	h					
transformer			no	15		
V Replacement of Gasket of	V					1
transformer of ratings	-	•				
650KVA/630KV/500KVA/315KVA no 7		0	no	7		
as per scope of work listed at			-			
			1	1		1
Total		2.1.14		Total		

Total (In Words)

Rupees\_

\_\_\_\_ only.

## Note:

- 1. The offered rates shall be exclusive of GST.
- 2. Payment will be done as per the actual work carried out during the execution.

