



NOTES:

- ALL DIMENSIONS ARE IN mm
- FINISHED RUBBER FENDERS SHALL BE FREE FROM SURFACE IMPERFECTIONS, POROSITY, VOIDS INCLUDING FLOW MARKS Etc & DEFECTS WHICH WOULD IMPAIR SATISFACTORY PERFORMANCE.
- RUBBER SHORE HARDNESS TO BE IRHD 60<sup>±4</sup>
- THE DESIGN OF FENDERS AND MATERIALS USED SHALL CONFORM TO BS-6349, 1985, PART IV.
- LINEAR TOLERANCES TO RUBBER FENDERS SHALL BE +0.2 TO FACILITATE EASY FIXATION OF FENDERS BETWEEN SKIRTING PLATES.
- TOTAL LENGTH OF W TYPE RUBBER FENDER = 36.5 Mt<sub>0</sub>/TUG.
- TOTAL LENGTH OF CYLINDRICAL HOLLOW TYPE RUBBER FENDER = 15 Mt<sub>0</sub>/TUG.
- ELE NO. 59 IS A STRAIGHT PIECE OF LENGTH 3200mm.
- SUPPLIER IS ADVISED TO SUPPLY MOULDED LENGTH IN ONE OR TWO PIECES FOR ELE 60 & 61.

ASBUILT  
NAME OF THE VESSEL: TIRACOL II  
BUILT FOR: MORMUGAO PORT TRUST

NET WT. Kg	NO	LOG
DRAWN	S. NAIDU	07.01.03
CHECKED		
APPROVED		

INDUSTAN SHIPYARD LTD., VISAKHAPATNAM, INDIA  
SCALE AS SHOWN  
SHIP NO: 1172  
DEPT. W.D.D.  
DRAWING NO. 39002  
Sheet No. 1 of 1